


Rohrkabelschuhe, 45° abgewinkelt

STANDARDSERIE

Werkstoff: E-Cu Rohr nach DIN 40 500 Oberfläche: galvanisch verz.



Querschnitt mm ²	Anschluss	Type	d1 mm	d2 mm	d3 mm	l mm	a mm	VPE
10	M 5	KRW 10- 5/45°	4,3	5,3	10,0	10,0		100
	M 6	KRW 10- 6/45°		6,4	11,0			100
	M 8	KRW 10- 8/45°		8,4	15,0			100
16	M 6	KRW 16- 6/45°	5,4	6,4	11,3	11,0		100
	M 8	KRW 16- 8/45°		8,4	15,0			100
	M 10	KRW 16-10/45°		10,5	18,0			100
25	M 6	KRW 25- 6/45°	6,9	6,4	14,0	13,0		100
	M 8	KRW 25- 8/45°		8,4	15,0			100
	M 10	KRW 25-10/45°		10,5	18,0			100
	M 12	KRW 25-12/45°		13,0	20,0			100
35	M 6	KRW 35- 6/45°	5,3	6,4	16,5	16,0		50
	M 8	KRW 35- 8/45°		8,4	16,5			50
	M 10	KRW 35-10/45°		10,5	18,0			50
	M 12	KRW 35-12/45°		13,0	20,0			50
50	M 8	KRW 50- 8/45°	9,6	8,4	19,0	18,0		50
	M 10	KRW 50-10/45°		10,5	20,0			50
	M 12	KRW 50-12/45°		13,0	23,0			50
70	M 8	KRW 70- 8/45°	11,5	8,4	22,0	21,0		25
	M 10	KRW 70-10/45°		10,5	22,0			25
	M 12	KRW 70-12/45°		13,0	23,0			25
95	M 8	KRW 95- 8/45°	13,5	8,4	25,0	24,0		25
	M 10	KRW 95-10/45°		10,5	25,0			25
	M 12	KRW 95-12/45°		13,0	25,0			25
120	M 10	KRW 120-10/45°	15,5	10,5	29,0	28,0		25
	M 12	KRW 120-12/45°		13,0	29,0			25
	M 16	KRW 120-16/45°		17,0	29,0			25
150	M 10	KRW 150-10/45°	16,8	10,5	32,0	29,0		25
	M 12	KRW 150-12/45°		13,0	31,0			25
	M 16	KRW 150-16/45°		17,0	31,0			25
185	M 12	KRW 185-12/45°	19,0	13,0	35,0	30,0		25
	M 16	KRW 185-16/45°		17,0	35,0			25
	M 20	KRW 185-20/45°		21,0	35,0			25
240	M 12	KRW 240-12/45°	21,0	13,0	38,0	38,0		25
	M 16	KRW 240-16/45°		17,0	38,0			25
	M 20	KRW 240-20/45°		21,0	38,0			25

