

Rohrkabelschuhe EURO-SERIE

Querschnitt mm ²	Anschluss	Type	d1 mm	d2 mm	d3 mm	l mm	a mm	
120	M 8	KRTE 120- 8	15,0	8,4	29,0	49,5	28,0	VPE
	M 10	KRTE 120-10		10,5	29,0	52,0		
	M 12	KRTE 120-12		13,0	29,0	51,5		
	M 16	KRTE 120-16		17,0	30,0	55,0		
150	M 10	KRTE 150-10	16,5	10,5	32,0	55,5	30,0	
	M 12	KRTE 150-12		13,0	32,0	58,0		
	M 16	KRTE 150-16		17,0	32,0	61,0		
	M 20	KRTE 150-20		21,0	35,0	63,5		
185	M 10	KRTE 185-10	19,0	10,5	35,0	59,0	30,0	
	M 12	KRTE 185-12		13,0	35,0	58,5		
	M 16	KRTE 185-16		17,0	35,0	61,0		
	M 20	KRTE 185-20		21,0	35,0	66,0		
240	M 10	KRTE 240-10	21,0	10,5	38,0	67,0	35,0	
	M 12	KRTE 240-12		13,0	38,0	67,0		
	M 16	KRTE 240-16		17,0	38,0	69,5		
	M 20	KRTE 240-20		21,0	38,0	71,0		
300	M 12	KRTE 300-12	24,0	13,0	44,0	82,0	42,0	
	M 16	KRTE 300-16		15,0	44,0	84,0		
	M 20	KRTE 300-20		17,0	43,8	85,0		
400	M 12	KRTE 400-12	27,5	10,5	49,0	92,0	47,0	
	M 16	KRTE 400-16		13,0	49,0	92,0		
	M 20	KRTE 400-20		17,0	49,0	92,0		

Stoßverbinder EURO-SERIE

(= kompatibel zu vielen anderen Fabrikaten)

Werkstoff: E-Cu Rohr nach DIN 40 500 Oberfläche: galvanisch verzinkt



Querschnitt mm ²	Type	d1 mm	l mm	VPE
0,75	KSRE 0,75	1,40	14	100
1,5	KSRE 1,50	1,90	14	100
2,5	KSRE 2,50	2,40	16	100
4	KSRE 4,00	3,00	19	100
6	KSRE 6,00	3,70	25	100
10	KSRE 10	4,50	31	100
16	KSRE 16	5,50	35	100
25	KSRE 25	7,00	50	100
35	KSRE 35	8,50	55	100
50	KSRE 50	10,00	70	50
70	KSRE 70	12,00	75	50
95	KSRE 95	13,50	75	50
120	KSRE 120	15,00	85	25
150	KSRE 150	16,50	85	25
185	KSRE 185	18,50	100	25
240	KSRE 240	21,00	100	25

