


# Rohrkabelschuhe - STANDARDSERIE

Werkstoff: E-Cu Rohr nach DIN 40 500 Oberfläche: galvanisch verzinkt



Querschnitt mm <sup>2</sup>	Anschluss	Type	d1 mm	d2 mm	d3 mm	l mm	a mm	VPS
35	M 5	KRT 35- 5	8,3	5,3	16,5	31,5	16,0	100
	M 6	KRT 35- 6		6,4	16,5	32,5		100
	M 8	KRT 35- 8		8,4	16,5	33,0		100
	M 10	KRT 35-10		10,5	18,0	35,5		100
	M 12	KRT 35-12		13,0	20,0	36,5		100
	M 16	KRT 35-16		17,0	26,0	41,5		100
50	M 6	KRT 50- 6	9,6	6,4	19,0	36,0	18,0	50
	M 8	KRT 50- 8		8,4	19,0	37,0		50
	M 10	KRT 50-10		10,5	20,0	39,0		50
	M 12	KRT 50-12		13,0	23,0	40,5		50
	M 16	KRT 50-16		17,0	27,0	45,5		50
	M 20	KRT 50-20		21,0	28,0	50,0		50
70	M 6	KRT 70- 6	11,5	6,4	22,5	41,0	21,0	25
	M 8	KRT 70- 8		8,4	22,5	41,0		25
	M 10	KRT 70-10		10,5	22,0	42,5		25
	M 12	KRT 70-12		13,0	23,0	43,5		25
	M 16	KRT 70-16		17,0	28,0	48,5		25
95	M 8	KRT 95- 8	13,5	8,4	25,0	45,5	24,0	25
	M 10	KRT 95-10		10,5	25,0	47,0		25
	M 12	KRT 95-12		13,0	26,0	47,0		25
	M 16	KRT 95-16		17,0	28,0	50,0		25
120	M 8	KRT 120- 8	15,5	8,4	29,0	50,5	28,0	25
	M 10	KRT 120-10		10,5	29,0	53,0		25
	M 12	KRT 120-12		13,0	29,0	52,5		25
	M 16	KRT 120-16		17,0	29,0	55,0		25
150	M 10	KRT 150-10	16,8	10,5	31,0	56,5	29,0	25
	M 12	KRT 150-12		13,0	31,0	56,0		25
	M 16	KRT 150-16		17,0	31,0	58,0		25
	M 20	KRT 150-20		21,0	35,0	63,0		25
185	M 10	KRT 185-10	19,0	10,5	35,0	59,0	30,0	25
	M 12	KRT 185-12		13,0	35,0	58,5		25
	M 16	KRT 185-16		17,0	35,0	63,0		25
	M 20	KRT 185-20		21,0	35,0	66,0		25
240	M 10	KRT 240-10	21,0	10,5	38,0	67,0	38,0	25
	M 12	KRT 240-12		13,0	38,0	67,0		25
	M 16	KRT 240-16		17,0	38,0	69,5		25
	M 20	KRT 240-20		21,0	38,0	71,0		25

