


Rohrkabelschuhe - STANDARDSERIE

Werkstoff: E-Cu Rohr nach DIN 40 500 Oberfläche: galvanisch verzinkt

Querschnitt mm ²	Anschluss	Type	d1 mm	d2 mm	d3 mm	l mm	a mm	VPS
300	M 12	KRT 300-12	24,0	13,0	44,0	82,0	42,0	25
	M 16	KRT 300-16		17,0	44,0	85,0		25
	M 20	KRT 300-20		21,0	44,0	85,0		25
400	M 12	KRT 400-12	27,5	13,0	49,0	92,0	47,0	25
	M 16	KRT 400-16		17,0	49,0	92,0		25
	M 20	KRT 400-20		21,0	49,0	92,0		25



Stoßverbinder - Rohrausführung

Werkstoff: E-Cu Rohr nach DIN 40 500 Oberfläche: galvanisch verzinkt

Querschnitt mm ²	Type	d1 mm	l mm	VPE
0,75	KSR 0,75	1,40	14	100
1,5	KSR 1,50	1,90	14	100
2,5	KSR 2,50	2,40	16	100
4	KSR 4,00	3,00	19	100
6	KSR 6,00	3,70	19	100
10	KSR 10	4,30	30	100
16	KSR 16	5,40	35	100
25	KSR 25	6,90	40	100
35	KSR 35	8,30	45	100
50	KSR 50	9,60	50	100
70	KSR 70	11,50	55	50
95	KSR 95	13,50	60	50
120	KSR 120	15,50	65	50
150	KSR 150	16,80	70	25
185	KSR 185	19,00	80	25
240	KSR 240	21,00	90	25
300	KSR 300	24,00	100	25
400	KSR 400	27,50	100	25

