


# Rohrkabelschuhe, 90° abgewinkelt

## STANDARDSERIE

Werkstoff: E-Cu Rohr nach DIN 40 500 Oberfläche: galvanisch verzinkt



Querschnitt mm <sup>2</sup>	Anschluss	Type	d1 mm	d2 mm	d3 mm	l mm	a mm	VPE
35	M 6	KRW 35- 6/90°	8,3	6,4	16,5	16,2	16,0	100
	M 8	KRW 35- 8/90°		8,4	16,5	18,2		100
	M 10	KRW 35-10/90°		10,5	18,0	20,2		100
	M 12	KRW 35-12/90°		13,0	20,0	21,2		100
50	M 6	KRW 50- 6/90°	9,6	6,4	19,0	17,1	18,0	100
	M 8	KRW 50- 8/90°		8,4	19,0	19,1		100
	M 10	KRW 50-10/90°		10,5	20,0	21,1		100
	M 12	KRW 50-12/90°		13,0	23,0	23,5		100
	M 16	KRW 50-16/90°		17,0	28,0	25,1		100
70	M 8	KRW 70- 8/90°	11,5	8,4	22,0	20,2	21,0	50
	M 10	KRW 70-10/90°		10,5	22,0	22,2		50
	M 12	KRW 70-12/90°		13,0	23,0	23,2		50
	M 16	KRW 70-16/90°		17,0	28,0	26,2		50
95	M 8	KRW 95- 8/90°	13,5	8,4	25,0	21,3	24,0	50
	M 10	KRW 95-10/90°		10,5	25,0	23,3		50
	M 12	KRW 95-12/90°		13,0	25,0	24,3		50
	M 16	KRW 95-16/90°		17,0	28,0	27,3		50
120	M 10	KRW 120-10/90°	15,5	10,5	29,0	25,0	28,0	25
	M 12	KRW 120-12/90°		13,0	29,0	26,0		25
	M 16	KRW 120-16/90°		17,0	29,0	29,0		25
150	M 10	KRW 150-10/90°	16,8	10,5	31,0	25,7	29,0	25
	M 12	KRW 150-12/90°		13,0	31,0	26,7		25
	M 16	KRW 150-16/90°		17,0	31,0	29,7		25
185	M 10	KRW 185-10/90°	19	10,5	35,0	27,0	30,0	25
	M 12	KRW 185-12/90°		13,0	35,0	28,0		25
	M 16	KRW 185-16/90°		17,0	35,0	31,0		25
	M 20	KRW 185-20/90°		21,0	35,0	35,0		25
240	M 12	KRW 240-12/90°	21,0	13,0	38,0	29,0	38,0	25
	M 16	KRW 240-16/90°		17,0	38,0	32,0		25
	M 20	KRW 240-20/90°		21,0	38,0	36,0		25

