


Rohrkabelschuhe, 90° abgewinkelt, EURO-SERIE

(=kompatibel zu vielen anderen Fabrikaten), Ringform

Werkstoff: E-Cu Rohr nach DIN 40 500 Oberfläche: galvanisch verzinkt



Querschnitt mm ²	Anschluss	Type	d1 mm	d2 mm	d3 mm	l mm	a mm	VPE
6	M 5	KRWE 6- 5/90°	3,5	5,5	10,0	21,0	9,0	100
	M 6	KRWE 6- 6/90°		6,5	12,0	21,0		100
	M 8	KRWE 6- 8/90°		8,5	15,0	23,0		100
10	M 5	KRWE 10- 5/90°	4,5	5,3	12,0	12,5	10,0	100
	M 6	KRWE 10- 6/90°		6,4	12,0	13,5		100
	M 8	KRWE 10- 8/90°		8,4	15,0	15,5		100
	M 10	KRWE 10-10/90°		10,5	18,0	17,5		100
	M 12	KRWE 10-12/90°		13,0	20,0	19,0		100
16	M 5	KRWE 16- 5/90°	5,5	5,3	12,0	13,2	13,0	100
	M 6	KRWE 16- 6/90°		6,4	14,0	14,3		100
	M 8	KRWE 16- 8/90°		8,4	15,0	16,3		100
	M 10	KRWE 16-10/90°		10,5	18,0	18,3		100
	M 12	KRWE 16-12/90°		13,0	20,0	19,3		100
25	M 6	KRWE 25- 6/90°	7	6,4	15,0	15,8	18,0	100
	M 8	KRWE 25- 8/90°		8,4	16,0	17,8		100
	M 10	KRWE 25-10/90°		10,5	18,0	19,8		100
	M 12	KRWE 25-12/90°		13,0	20,0	20,8		100
35	M 6	KRWE 35- 6/90°	8,5	6,4	17,0	16,5	19,0	100
	M 8	KRWE 35- 8/90°		8,4	17,0	18,5		100
	M 10	KRWE 35-10/90°		10,5	20,0	20,5		100
	M 12	KRWE 35-12/90°		13,0	20,0	21,5		100
50	M 6	KRWE 50- 6/90°	10	6,4	20,0	17,5	20,0	100
	M 8	KRWE 50- 8/90°		8,4	20,0	19,5		100
	M 10	KRWE 50-10/90°		10,5	20,0	21,5		100
	M 12	KRWE 50-12/90°		13,0	23,0	22,5		100
	M 16	KRWE 50-16/90°		17,0	27,0	25,5		100
70	M 8	KRWE 70- 8/90°	12	8,4	24,0	20,8	21,0	25
	M 10	KRWE 70-10/90°		10,5	24,0	22,8		25
	M 12	KRWE 70-12/90°		13,0	24,0	23,8		25
	M 16	KRWE 70-16/90°		17,0	28,0	26,8		25
95	M 8	KRWE 95- 8/90°	13,5	8,4	26,0	21,5	23,0	25
	M 10	KRWE 95-10/90°		10,5	26,0	23,5		25
	M 12	KRWE 95-12/90°		13,0	26,0	24,5		25
	M 16	KRWE 95-16/90°		17,0	28,0	27,5		25
120	M 10	KRWE 120-10/90°	15,0	10,5	29,0	25,0	28,0	25
	M 12	KRWE 120-12/90°		13,0	29,0	26,0		25
	M 16	KRWE 120-16/90°		17,0	30,0	29,0		25

