

## Rohrkabelschuhe, 45° abgewinkelt, EURO-SERIE

(=kompatibel zu vielen anderen Fabrikaten), Ringform

Werkstoff:E-Cu Rohr nach DIN 40 500 Oberfläche:galvanisch verzinkt

Querschnitt mm <sup>2</sup>	Anschluss	Type	d1 mm	d2 mm	d3 mm	l mm	a mm	VPE
								VPE
70	M 8	KRWE 70- 8/45°	12,0	8,4	24,0	20,0		25
	M 10	KRWE 70-10/45°		10,5	24,0			25
	M 12	KRWE 70-12/45°		13,0	24,0			25
95	M 8	KRWE 95- 8/45°	13,5	8,4	26,0	22,0		25
	M 10	KRWE 95-10/45°		10,5	26,0			25
	M 12	KRWE 95-12/45°		13,0	26,0			25
120	M 8	KRWE 120- 8/45°	15,0	8,4	29,0	25,0		25
	M 10	KRWE 120-10/45°		10,5	29,0			25
	M 12	KRWE 120-12/45°		13,0	29,0			25
	M 16	KRWE 120-16/45°		17,0	30,0			25
150	M 10	KRWE 150-10/90°	16,5	10,5	32,0	29,0		25
	M 12	KRWE 150-12/90°		13,0	32,0			25
	M 16	KRWE 150-16/90°		17,0	32,0			25
185	M 10	KRWE 185-10/45°	19,0	10,5	35,0	29,0		25
	M 12	KRWE 185-12/45°		13,0	35,0			25
	M 16	KRWE 185-16/45°		17,0	35,0			25
	M 20	KRWE 185-20/45°		21,0	35,0			25
240	M 12	KRWE 240-12/45°	21,0	13,0	38,0	34,0		25
	M 16	KRWE 240-16/45°		17,0	38,0			25
	M 20	KRWE 240-20/45°		21,0	38,0			25

