


# Rohrkabelschuhe für feindrätige Leiter

Werkst.: E-Cu Rohr nach DIN 40 500 Oberfläche: galvanisch verzinkt, Ringform



Querschnitt mm <sup>2</sup>	Anschluss	Type	d1 mm	d2 mm	d3 mm	l mm	a mm	VPE
								VPE
10	M 5	KRF 10- 5	5,0	5,3	12,0	23,0	12,0	100
	M 6	KRF 10- 6		6,4	12,0	25,0		100
	M 8	KRF 10- 8		8,4	15,0	28,0		100
	M 10	KRF 10-10		10,5	18,0	31,0		100
	M 12	KRF 10-12		13,0	20,0	32,0		100
16	M 5	KRF 16- 5	6,0	5,3	14,0	25,5	13,0	100
	M 6	KRF 16- 6		6,4	14,0	27,0		100
	M 8	KRF 16- 8		8,4	15,0	29,5		100
	M 10	KRF 16-10		10,5	18,0	32,0		100
	M 12	KRF 16-12		13,0	20,0	32,5		100
25	M 6	KRF 25- 6	7,7	6,4	16,0	32,0	16,0	100
	M 8	KRF 25- 8		8,4	16,0	34,0		100
	M 10	KRF 25-10		10,5	18,0	35,0		100
	M 12	KRF 25-12		13,0	20,0	36,0		100
35	M 6	KRF 35- 6	9,0	6,4	18,0	36,0	18,0	100
	M 8	KRF 35- 8		8,4	18,0	36,0		100
	M 10	KRF 35-10		10,5	20,0	38,0		100
	M 12	KRF 35-12		13,0	23,0	40,0		100
	M 16	KRF 35-16		17,0	28,0	45,0		100
50	M 6	KRF 50- 6	11,0	6,4	22,0	42,0	21,0	100
	M 8	KRF 50- 8		8,4	22,0	42,0		100
	M 10	KRF 50-10		10,5	22,0	43,0		100
	M 12	KRF 50-12		13,0	23,0	44,0		100
	M 16	KRF 50-16		17,0	28,0	48,5		100
70	M 8	KRF 70- 8	13,5	8,4	25,0	47,0	24,0	50
	M 10	KRF 70-10		10,5	25,0	48,0		50
	M 12	KRF 70-12		13,0	26,0	48,0		50
	M 16	KRF 70-16		17,0	28,0	52,0		50
	M 20	KRF 70-20		21,0	31,0	55,5		50
95	M 10	KRF 95-10	15,5	10,5	29,0	55,0	28,0	50
	M 12	KRF 95-12		13,0	29,0	54,5		50
	M 16	KRF 95-16		17,0	29,0	57,0		50
	M 20	KRF 95-20		21,0	35,0	62,0		50
120	M 10	KRF 120-10	16,8	10,5	31,0	56,5	29,0	50
	M 12	KRF 120-12		13,0	31,0	56,0		50
	M 16	KRF 120-16		17,0	31,0	57,5		50
	M 20	KRF 120-20		21,0	35,0	63,0		50
150	M 10	KRF 150-10	19,0	10,5	35,0	61,0	30,0	25
	M 12	KRF 150-12		13,0	35,0	61,0		25
	M 16	KRF 150-16		17,0	35,0	63,0		25
	M 20	KRF 150-20		21,0	35,0	66,0		25

