


## Presskabelschuhe nach DIN 46235

Werkstoff: E-Cu Rohr nach DIN 40 500 Oberfläche: galvanisch verzinkt



Ringform									
Querschnitt mm <sup>2</sup>	Anschluss	Type	d1 mm	d2 mm	d3 mm	l mm	a mm	VPE VPE	d1
150	M 10	PKS 150-10	17,0	10,5	34,0	79,0	35,0	25	
	M 12	PKS 150-12		13,0	34,0	78,5		25	
	M 16	PKS 150-16		17,0	34,0	78,0		25	
	M 20	PKS 150-20		21,0	38,0	78,0		25	
185	M 10	PKS 185-10	25,0	10,5	37,0	83,0	40,0	25	
	M 12	PKS 185-12		13,0	37,0	82,5		25	
	M 16	PKS 185-16		17,0	37,0	82,0		25	
	M 20	PKS 185-20		21,0	40,0	83,0		25	
240	M 10	PKS 240-10	28,0	21,5	10,5	92,0	40,0	25	
	M 12	PKS 240-12		13,0	42,5	92,0		25	
	M 16	PKS 240-16		17,0	42,5	92,0		25	

## Pressverbinder nach DIN 46267

Werkstoff: E-Cu, Oberfläche: galvanisch verzinkt



Querschnitt mm <sup>2</sup>	Type	d1 mm	l mm	VPE
6	KSP 6	3,7	30,0	100
10	KSP 10	4,4	30,0	100
16	KSP 16	5,5	50,0	100
25	KSP 25	7,0	50,0	100
35	KSP 35	8,2	50,0	100
50	KSP 50	10,0	56,0	50
70	KSP 70	11,5	56,0	50
95	KSP 95	13,5	70,0	50
120	KSP 120	15,5	70,0	25
150	KSP 150	17,0	80,0	25
185	KSP 185	19,0	85,0	25
240	KSP 240	21,5	90,0	25

