


Aderendhülsen, nicht isoliert nach DIN 46228 Teil 1

Werkstoff: E-Cu Rohr, Oberfläche: galvanisch verzinkt



Querschnitt mm ²	Type	d1 mm	l1 mm	VPE VPE
0,25	AE 0,25- 5	0,8	5,0	1000
	AE 0,25- 7		7,0	1000
0,34	AE 0,34- 5	0,8	5,0	1000
	AE 0,34- 7		7,0	1000
0,50	AE 0,50- 6	1,1	6,0	1000
	AE 0,50- 8		8,0	1000
	AE 0,50-10		10,0	1000
	AE 0,50-12		12,0	1000
0,75	AE 0,75- 6	1,25	6,0	1000
	AE 0,75- 8		8,0	1000
	AE 0,75-10		10,0	1000
	AE 0,75-12		12,0	1000
1,00	AE 1- 6	1,5	6,0	1000
	AE 1- 8		8,0	1000
	AE 1-10		10,0	1000
	AE 1-12		12,0	1000
1,5	AE 1,5- 7	1,9	7,0	1000
	AE 1,5-10		10,0	1000
	AE 1,5-12		12,0	1000
	AE 1,5-15		15,0	500
	AE 1,5-18		18,0	500
2,5	AE 2,5- 7	2,3	7,0	1000
	AE 2,5-10		10,0	1000
	AE 2,5-12		12,0	1000
	AE 2,5-15		15,0	500
	AE 2,5-18		18,0	500
4	AE 4- 9	2,9	9,0	1000
	AE 4-12		12,0	1000
	AE 4-15		15,0	500
	AE 4-18		18,0	500
6	AE 6-10	3,7	10,0	500
	AE 6-12		12,0	500
	AE 6-15		15,0	500
	AE 6-18		18,0	500
	AE 6-20		20,0	500

