

Aderendhülsen, nicht isoliert nach DIN 46228 Teil 1

Werkstoff:E-Cu Rohr, Oberfläche:galvanisch verzinkt

Querschnitt mm ²	Type	d1 mm	l1 mm	VPE
				VPE
10	AE 10-12	4,6	12,0	500
	AE 10-15		15,0	500
	AE 10-18		18,0	100
	AE 10-20		20,0	100
16	AE 16-12	6,0	12,0	100
	AE 16-15		15,0	100
	AE 16-18		18,0	100
	AE 16-25		25,0	100
	AE 16-32		32,0	100
25	AE 25-12	7,5	12,0	100
	AE 25-15		15,0	100
	AE 25-18		18,0	100
	AE 25-22		22,0	100
	AE 25-25		25,0	100
	AE 25-32		32,0	100
35	AE 35-18	8,5	18,0	100
	AE 35-22		22,0	100
	AE 35-25		25,0	100
	AE 35-32		32,0	100
50	AE 50-18	10,5	18,0	100
	AE 50-22		22,0	100
	AE 50-25		25,0	100
	AE 50-32		32,0	100
70	AE 70-25	12,7	25,0	100
	AE 70-32		32,0	100
95	AE 95-25	14,7	25,0	100
	AE 95-32		32,0	100
120	AE 120-32	16,7	32,0	100
	AE 120-40		40,0	100
150	AE 150-32	18,7	32,0	100
	AE 150-40		40,0	100
185	AE 185-40	20,2	40,0	100
240	AE 240-34	23,0	34,0	100
	AE 240-40		40,0	100

